

8-port Gigabit Ethernet Switch (Plastic Shell)



Product Highlights

- 8*1G RJ45 ports
- Compliant with IEEE802.3 and IEEE802.3u,IEEE802.3az,IEEE802.3ab standards
- RJ45 port supports 10M/100M/1G adaptive
- Supports automatic port flipping (Auto MDI/MDIX)
- The panel indicator LED will monitor the working status and assist in fault analysis
- Flow control method, IEEE802.3x standard for full duplex and Backpressure standard for half duplex

Hardware Features

Description	Specification
Model	EW-08G-5W-EP-P
Interface	8 *1G RJ45 ports
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3x (Flow Control) IEEE802.3ab (Gigabit Ethernet) IEEE802.3az(Energy Efficient Ethernet)
Switching Capacity	16Gbps
Packet Forwarding Rate	11.9Mpps
Packet Buffer	4Mbit
MAC Address Table	8K
Transmission Method	Store and Forward
Power Supply	AC 100-240V , 50/60Hz DC 5V 1A
Mainboard Power Consumption	3.77W
Structure Information	Product Dimensions :145*60*21.5mm Packaging Dimensions :146*88*55mm Product Net Weight:0.111Kg Product Gross Weight:0.166Kg
Packing Information	Carton Dimensions :580*475*315mm Packing Quantity: 100PCS Packing Weight:17.6KG
Package Contents	switch 1pcs, Power adapter 1pcs, manual 1pcs, certificate of qualification 1pcs
Fan Quantity	0
Installation	desktop
Surge Protection	Surge protection: common mode 2KV, differential mode 1KV
Operating Temperature	0~40°C
Storage Temperature	-40 °C to 70 °C
Operation Humidity	10%~90%, non condensing
Storage Humidity	5%~95%, non condensing
PWR LED	Green LED On: Powered on Green LED Off: Powered off
1-8 LED	Green LED On:Link normal Green LED Off: Link blocked Flashing: Data transmitting

Product Structure Diagram

