

Model	HD-U690-8H2G-96	
Product	PoE Switch with Standard PSE Chip	
Ports		
Network Port:	10	
PoE Port:	8, 10/100Mbps; RJ45 Ports; Max. 30W Output of Single PoE Port	
Uplink Port:	2, 1000Mbps; RJ45 Ports;Transmission Distance: Default: 0-100m	
PWR (Power supply Indicator)	Light on: Powering	
	Light off: No Power	
Mode (Slide Switch)	Green light off: Normal/Default mode	
	Green light on: VLAN mode	
	Green light flash: Extend mode	
1-10 Indicator	Green light off: Link is disconnected	
	Green light on: Link is connected	
	Green light flash: Data Transmitting	
Standard		
Network Protocol:	IEEE802.3/802.3u/IEEE 802.3ab/802.3x	
Performance		
Switching Capacity:	5.6Gbps (non-blocking)	
Packet Forwarding Rate:	4.166Mpps	
Forwarding Mode:	Store-and-forward	
Packet Buffer:	448K	
MAC Address Table:	2K	
VLAN	Support	
PoE watch dog	Support	
Power Over Ethernet		
PoE Standard:	IEEE802.3af, IEEE802.3at	
PoE Power Supply	1/2(+),3/6(-)	
Transmission Distance:	0-100m/100Mbps or Max. 250m/10Mbps via Cat.5e or more under Extend mode	
General		
Power Source:	Bult-in Power Supply	
	Input: 100-240VAC, 50/60Hz	
PoE Power Budget:	96W	
Power Consumption:	<5W	
ESD	Air discharge: 15KV	
	Contact discharge: 8KV	
Surge Protecton -RJ45 Port	Common mode: 6KV	
	Differential mode/PoE : 6KV	
	Differential mode/Signal: 6KV	

Surge Protection -Power Supply	Common mode: 6KV Differential mode: 2KV
Working Temperature:	-10°C-45°C
Humidity:	10%-90% , non-condensing
Storage Temperature:	-40°C-70°C
Color	Black
Weight:	0.68kg (not include input cable & packaging)
Dimension(L×W×H):	200*118*44mm

Product Picture

