

<b>Model</b>	HD-U890-8G2G-96
Product	PoE Switch with Standard PSE Chip
<b>Ports</b>	
Network Port:	10
PoE Port:	8, 1000Mbps; RJ45 ports; Max. 30W Output of Single PoE Port
Uplink Port:	2, 1000Mbps; Transmission Distance: Default: 0-100m
PWR (Power supply Indicator)	Light on: Powering Light off: No Power
Mode (Slide Switch)	Green light off: Normal/Default mode
	Green light on: VLAN mode
	Green light flash: Extend mode
1-10 Indicator	Green light off: Link is disconnected
	Green light on: Link is connected
	Green light flash: Data Transmitting
<b>Standard</b>	
Network Protocol:	IEEE802.3i/802.3u/802.3x/802.3af/802.3ab
<b>Performance</b>	
Switching Capacity:	20 Gbps Full duplex
Packet Forwarding Rate:	1.488Mpps/port
Forwarding Mode:	Store-and-forward
MAC Address Table:	2K
VLAN	Support
Watchdog	Support
<b>Power Over Ethernet</b>	
PoE Standard:	IEEE802.3af, IEEE802.3at
PoE Power Supply	1/2(+),3/6(-)
Transmission Distance:	0-100m/1000Mbps or Port 7-8 Max. 250m/10Mbps via Cat.5e or more under Extend mode
PoE Feature	All ports support MDI/MDIX
<b>General</b>	
Power Source:	Bult-in Power Supply
	Input: 100-240VAC, 50/60Hz
PoE Power Budget:	96W
Power Consumption:	<5W
ESD	Air discharge: 15KV
	Contact discharge: 8KV
Surge Protecton -RJ45 Port	Common mode: 6KV
	Differential mode/PoE : 6KV
	Differential mode/Signal: 6KV
Surge Protecton	Common mode: 6KV

-Power Supply	Differential mode: 2KV
Color	Black
Weight:	0.73 kg (not include input cable & packaging)
Dimension(L×W×H):	200*118*44 mm

### Product Picture

