

Model	HD-U890-8G2G2F-96	
Product	PoE Switch with Standard PSE Chip	
Ports		
Port:	12	
PoE Port:	8, 1000Mbps; RJ45 ports; Max. 30W Output of Single PoE Port	
Uplink Port:	2*1000Mbps RJ45 ports + 2*1000Mbps SFP ports; Transmission Distance: Default: 0-100m	
PWR (Power supply Indicator)	Light on: Powering	
	Light off: No Power	
Mode (Slide Switch)	Green light off: Normal/Default mode	
	Green light on: VLAN mode	
	Green light flash: Extend mode	
1-12 ACT Indicator	Green light off: Link is disconnected	
	Green light on: Link is connected	
	Green light flash: Data Transmitting	
Standard		
Network Protocol:	IEEE802.3i/802.3u/802.3x/802.3af/802.3ab/ IEEE 802.3z	
Performance		
Switching Capacity:	24Gbps Full duplex	
Packet Forwarding Rate:	1.488Mpps/port	
Forwarding Mode:	Store-and-forward	
MAC Address Table:	2K	
VLAN	Support	
Watchdog	Support	
Power Over Ethernet		
PoE Standard:	IEEE802.3af, IEEE802.3at	
PoE Power Supply	1/2(+),3/6(-)	
Transmission Distance:	0-100m/1000Mbps or Port 7-8 Max. 250m/10Mbps via Cat.5e or more under Extend mode	
PoE Feature	All ports support MDI/MDIX	
General		
Power Source:	Bult-in Power Supply	
	Input: 100-240VAC, 50/60Hz	
PoE Power Budget:	96W	
Power Consumption:	<5W	
ESD	Air discharge: 15KV	
	Contact discharge: 8KV	
Surge Protecton -RJ45 Port	Common mode: 6KV	
	Differential mode: 6KV	
Surge Protecton	Common mode: 6KV	

-Power Supply	Differential mode: 2KV
Color	Black
Weight:	0.95 kg (not include input cable & packaging)
Dimension(LxWxH):	220*161*44 mm

Product Picture

