

<b>Model</b>	HD-U990-4H2-48
<b>Product</b>	PoE Switch with Standard PSE Chip
<b>Ports</b>	
Network Port:	6
PoE Port:	4, 10/100Mbps; RJ45 port; Max. 30W Output of Single PoE Port
Uplink Port:	2, 10/100Mbps; Transmission Distance: Default: 0-100m
PWR (Power supply)	Light on: Powering
	Light off: No Power
Mode (Slide Switch)	Green light off: Normal/Default mode
	Green light on: VLAN mode
	Green light flash: Extend mode
1-6 Indicator	Green light off: Link is disconnected
	Green light on: Link is connected
	Green light flash: Data Transmitting
<b>Standard</b>	
Network Protocol:	IEEE802.3/802.3u/802.3x
<b>Performance</b>	
Switching Capacity:	1.2Gbps (non-blocking)
Packet Forwarding	0.1488Mpps/port
Forwarding Mode:	Store-and-forward
MAC Address Table:	2K
Extend mode	Support
VLAN mode	Support
PoE watch dog	Support
<b>Power Over Ethernet</b>	
PoE Standard:	IEEE802.3af, IEEE802.3at
PoE Power Supply	1/2(+),3/6(-)
Transmission	0-100m/100Mbps or Max. 250m/10Mbps via Cat.5e or more under
<b>General</b>	
Power Source:	Built-in Power Supply
	Input: 100-240VAC, 50/60Hz, Max. 1.5A @ 100V & Max. 0.8A @240V
PoE Power Budget:	48W
Power Consumption:	<5W

ESD	Air discharge: 15KV
	Contact discharge: 8KV
Surge Protection -RJ45 Port	Common mode: 6KV
	Differential mode/PoE : 6KV
	Differential mode/Signal: 6KV
Surge Protection -Power Supply	Common mode: 6KV
	Differential mode: 2KV
Working	-10°C-45°C
Working Humidity:	10%-90% , non-condensing
Storage	-40°C-70°C
Color	Black
Weight:	0.6kg(not include input cable & packaging)
Dimension(L×W×H):	200*118*44mm

### Product Picture

