

Model	HD-U990-8H2-96
Product	PoE Switch with Standard PSE Chip
Ports	
Network Port:	10
PoE Port:	8, 10/100Mbps; RJ45 ports; Max. 30W Output of Single PoE Port
Uplink Port:	2, 10/100Mbps; Transmission Distance: Default: 0-100m
PWR (Power supply Indicator)	Light on: Powering Light off: No Power
Mode (Slide Switch)	Green light off: Normal/Default mode
	Green light on: VLAN mode
	Green light flash: Extend mode
1-10 Indicator	Green light off: Link is disconnected
	Green light on: Link is connected
	Green light flash: Data Transmitting
Standard	
Network Protocol:	IEEE802.3/802.3u/802.3x
Performance	
Switching Capacity:	2Gbps (non-blocking)
Packet Forwarding Rate:	0.1488Mpps/port
Forwarding Mode:	Store-and-forward
MAC Address Table:	2K
Extend mode	Support
VLAN	Support
PoE watch dog	Support
Power Over Ethernet	
PoE Standard:	IEEE802.3af, IEEE802.3at
PoE Power Supply	1/2(+),3/6(-)
Transmission Distance:	0-100m/100Mbps or Max. 250m/10Mbps via Cat.5e or more under Extend mode
General	
Power Source:	Built-in Power Supply
	Input: 100-240VAC, 50/60Hz, Max. 2.6A @ 100V & Max. 1.3A @240V
PoE Power Budget:	96W
Power Consumption:	<5W

ESD	Air discharge: 15KV
	Contact discharge: 8KV
Surge Protecton -RJ45 Port	Common mode: 6KV
	Differential mode/PoE : 6KV
	Differential mode/Signal: 6KV
Surge Protecton -Power Supply	Common mode: 6KV
	Differential mode: 2KV
Working Temperature:	-10°C-45°C
Working Humidity:	10%-90% , non-condensing
Storage Temperature:	-40°C-70°C
Color	Black
Weight:	0.65kg (not include input cable & packaging)
Dimension(L×W×H):	200*118*44mm

Product Picture

